

WICKED GOOD PAINT COMPANY



100% ACRYLIC WATERBORNE CERAMIC

This premium waterborne 100% acrylic/ceramic reinforced interior finish incorporates the latest in coatings technology today. Its unique formulation provides exceptional hiding power along with outstanding product attributes. The ceramic additive provides additional stain resistance, durability and washability that separate this finish from standard acrylic paint technology. Ease of application, featuring anti-spatter additives sets the standard for flow, leveling and adhesion. It provides excellent color retention, non-yellowing film and moisture resistance, thus making it the ideal coating for any room in the home, office or commercial building.

RECOMMENDED USE: Use on all interior new or previously painted surfaces, such as wood, brick, stone, concrete, cement block, plaster, wallboard and other drywall construction as well as metal.

- High Hiding
- Mold & Mildew Resistance[†]
- Superior Washability

Available Bases & Sizes	Matte WG648			Eggshell WG649			Satin WG650			Semi Gloss WG651		
	Qt	Gal	5 Gal	Qt	Gal	5 Gal	Qt	Gal	5 Gal	Qt	Gal	5 Gal
Super Hide White 01							•	•		•	•	•
Base 1 1X	•	•	•	•	•	•				•	•	•
Base 2 2X				•	•							
Base 3 3X				•	•							
Base 4 4X				•	•							

Wicked Good Paint Company • wickedgoodpaint.com

Available exclusively at: Town Line Wallpaper & Paint Inc. 483 Broadway, Malden, MA 02148 • 781.324.9255 • townlinepaint.com

WICKED GOOD PAINT COMPANY



Ceramic Reinforced 100% Acrylic

Finish	Number	Product Type	Spread Rate	Dry Time	VOC Compliance
Matte	WG648	100% Acrylic Latex	Smooth: 350-400 sq. ft./gal Porous: 300-350 sq. ft./gal	To Touch: 1 hour To Handle: 8 hours To Recoat: 4-6 hours	EPA, OTC
Eggshell	WG649	100% Acrylic Latex	Smooth: 350-400 sq. ft./gal Porous: 300-350 sq. ft./gal	To Touch: 1 hour To Handle: 8 hours To Recoat: 4 hours	EPA, OTC
Satin	WG650	100% Acrylic Latex	Smooth: 350 - 400 sq. ft./gal Porous: 300-350 sq. ft./gal	To Touch: 1 hour To Handle: 8 hours To Recoat: 4-6 hours	EPA, OTC
Semi Gloss	WG651	100% Acrylic Latex	Smooth: 350 - 400 sq. ft./gal Porous: 300-350 sq. ft./gal	To Touch: 1 hour To Handle: 8 hours To Recoat: 4-6 hours	EPA, OTC

Spray application is 50% of above

@ 70°-77°F, 50% R.H.



†Contains an additive designed to inhibit growth of mold and mildew on the dried paint film only.



ABOUT US:

Town Line Wallpaper & Paint Inc Is Your Local Choice To Find Inspiration And Support About Your Paint And Stain Product Choices And Color Selections. We Are Dedicated To Serving Our Local Community Of Malden, Ma. Whether You Need Interior Or Exterior, High-End Or Commercial-Grade Coatings, We Are Ready To Serve You And Answer All Of Your Questions.

Rev. 11.19.21